

Milesight



Bullet ip camera of 2 megapixels and fix lens

MS-C2964-UPD

VIDEO (CAMERAS)

Video Resolution	2 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Anti fog system	Yes
Type of Codex	CBR / VBR
Bit rate	16Kbps ~ 16Mbps
Compression	H.265+ / H.265 / H.264
Main stream	1080P / 1.3Mpx / 720P / 704 x 576 (1 ~ 25fps)
Sub stream	704 x 576 / 640 x 480 / 640 x 360 / 352 x 288 (1 ~ 25fps)
Sub stream 2	720P / 704 x 576 / 640 x 480 / 640 x 360 / 352 x 288 (1 ~ 25fps)
Anti flap	Yes

IMAGE

Sensor	CMOS ®
Sensor resolution	1920 x 1080
Sensor Size	1/2.8"
Electronic shutter speed	1s to 1/100,000s
Minimum lighting	0.001Lux
Ratio S / N	More than 55dB

MATERIAL AND DIMENSIONS

Dimensions	160 x 64 x 64 mm
Material	Metal
Net weight	450 g

VIDEO ANALYSIS

Detection type	Analytical with human/vehicle classification in line/area crossing
Crossing line	Yes
Motion detection	Yes
Abandoned object	Yes
Missing object	Yes
Video Tamper	Yes
Loitering detection	Yes

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP67
Anti vandal	IK10
Use	Indoor-outdoor
Maximum humidity	90%

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S, G, T and Q
Management software	Milesight CMS
IP address filter	Yes
Network disconnection	Yes

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/1.0
Angle of View	109°

GENERAL INFORMATION

Serie	AI Color+ Series
Technology	IP
Type of camera	Bullet

NIGHT VISION

Night vision distance	30 m
-----------------------	------

technical datasheet

Weight with packaging	620 g
-----------------------	-------

DISTANCE DORI

Detect	40 m
Observe	16 m
Recognize	8 m
Identify	4 m

POWER CONSUMPTION

Consumption (w)	5W
PoE power	Yes
Type PoE	PoE 802.3af

STORAGE

MicroSD-Card	Up to 256Gb
Storage Systems	NAS / FTP / SFTP / Micro SD
ANR (Redundant Recording in SD)	Yes

Type of night vision	Luz blanca
----------------------	------------

White light	2
-------------	---

AXES

Motion	3-Axis
--------	--------

