



● **detnov**

Optical-thermal smoke sensor

DOTD-230A-I

AMBIENT

Operating temperature	-10 °C ~ 70 °C
Degree of protection	IP20
Use	Indoor
Maximum humidity	95%

POWER CONSUMPTION

Power mode	DC
Voltage	22V ~ 38V
Alarm Consumption	11mA

TECHNICAL SPECIFICATIONS

LED indicators	1
Short circuit isolator	Yes
Temperature activation	58°

CERTIFICATION

Normative **EN54-5 / EN54-7 / EN54-17**

MATERIAL AND DIMENSIONS

Dimensions	48 x 102 (Ø) mm
Material	ABS plastic
Net weight	100 g

GENERAL INFORMATION

Technology	Analog
Type	Optical-thermal smoke sensor

CONEXIONES (INCENDIO)

Cable	2 x 1.5 mm2
-------	--------------------



● detnov
DOTD-230A-I
 Addressable
 Opto-Heat Detector ISO
 V: 22-38 VDC Iq: 300µA
 doc. ref 5532/10/13
 EN 54-5:2017 + A1:2018
 EN 54-7:2018
 EN 54-17:2005 + AC:2007
 14-0370-CPR-1862
  
 1598612
 Made by Detnov in Spain (16/12/22)