

Milesight



Bullet ip camera of 5 megapixels and optical zoom lens

MS-C5364-FPE

VIDEO (CAMERAS)

| | |
|-------------------|---|
| Video Resolution | 5 Megapixels |
| BLC | Yes |
| HLC | Yes |
| 3D-NR | Yes |
| AGC | Yes |
| AWB | Yes |
| WDR | WDR (120 dB) |
| Images per second | 25fps |
| Video output | RJ45 |
| Day / night mode | Automatic / Manual |
| Privacy mask | Up to 8 zones |
| Anti fog system | Yes |
| Type of Codex | CBR / VBR |
| Bit rate | 16Kbps ~ 16Mbps |
| Compression | H.265+ / H.265 / H.264 |
| Main stream | 5Mpx / 3Mpx / 1080P / 1.3Mpx / 720P / 704 x 576 (1 ~ 25fps) |
| Sub stream | 704 x 576 / 640 x 480 / 640 x 360 / 352 x 288 / 320 x 240 (1 ~ 25fps) |
| Sub stream 2 | 1080P / 720P / 704 x 576 / 640 x 480 / 640 x 360 / 352 x 288 (1 ~ 25fps) |
| Watermark | Yes |
| Anti flap | Yes |

DISTANCE DORI

| | |
|-------------------------|--------------|
| Detect (Open lens) | 60 m |
| Detect (Closed Lens) | 192 m |
| Observe (Open lens) | 24 m |
| Observe (Closed lens) | 76 m |
| Recognize (Open lens) | 12 m |
| Recognize (Closed lens) | 39 m |
| Identify (Open lens) | 6 m |
| Identify (Closed lens) | 19 m |

POWER CONSUMPTION

VIDEO ANALYSIS

| | |
|--------------------------------|---|
| Detection type | Analytical with human/vehicle classification in line/area crossing |
| Funciones IA | Conteo de personas, mapa de calor, detección facial con metadatos |
| Crossing line | Yes |
| Face detection | Yes |
| Motion detection | Yes |
| Abandoned object | Yes |
| Missing object | Yes |
| Video Tamper | Sí |
| Heatmap | Yes |
| People counting | Yes |
| Loitering detection | Sí |
| Classification Human / vehicle | Yes |

IMAGE

| | |
|--------------------------|-------------------------|
| Sensor | CMOS ® |
| Sensor resolution | 2592 x 1944 |
| Sensor Size | 1/2.8' |
| Electronic shutter speed | 1s to 1/100,000s |
| Minimum lighting | 0.008 Lux |
| Ratio S / N | More than 55dB |

AMBIENT

| | |
|-----------------------|-----------------------|
| Operating temperature | -40 °C ~ 60 °C |
| Degree of protection | IP67 |
| Anti vandal | IK10 |
| Use | Indoor-outdoor |
| Maximum humidity | 95% |

LENS

| | |
|---------------------------|-------------------------|
| Lens Type | Optical zoom |
| Focal distance | 2.7 mm ~ 13.5 mm |
| Maximum diaphragm opening | F/1.4 |

technical datasheet

| | |
|-----------------|--------------------|
| Power mode | DC |
| Voltage | 12V |
| Consumption (w) | 9W |
| Amperage | 750mA |
| PoE power | Yes |
| Type PoE | PoE 802.3af |

NIGHT VISION

| | |
|-----------------------|-------------|
| Night vision distance | 50 m |
| Type of night vision | IR |
| Number of LEDs | 2 |
| Smart IR | Yes |
| Starlight | Yes |

NETWORK FEATURES

| | |
|-----------------------|--------------------------------|
| IP connection | 1 RJ45 (10M / 100M) |
| ONVIF | Yes, type S, G, T and Q |
| Management software | Milesight CMS |
| IP address filter | Yes |
| Network disconnection | Yes |

GENERAL INFORMATION

| | |
|----------------|------------------------------|
| Serie | AI Mini Camera Series |
| Technology | IP |
| Type of camera | Bullet |

AXES

| | |
|--------|---------------|
| Motion | 3-Axis |
|--------|---------------|

| | |
|---------------|------------------|
| Angle of View | 99° ~ 31° |
| Autofocus | Yes |

MATERIAL AND DIMENSIONS

| | |
|-----------------------|--------------------------|
| Dimensions | 239.5 x 76 (Ø) mm |
| Material | Metal |
| Net weight | 830 g |
| Weight with packaging | 1050 g |

STORAGE

| | |
|---------------------------------|-----------------------------|
| MicroSD-Card | Up to 256Gb |
| Storage Systems | NAS / FTP / Micro SD |
| Storage anomaly | Yes |
| ANR (Redundant Recording in SD) | Yes |

AUDIO(CAMERAS)

| | |
|--------------------|--|
| Audio compression | G.711 / G.722 / G.726 / AAC |
| Sampling frequency | 8 kHz 16 kHz 32 kHz 44.1 kHz 48 kHz |
| Bit rate | 16 Kbps ~ 256 Kbps |

SYSTEM (CAMERAS)

| | |
|--------------|------------|
| Reset button | Yes |
|--------------|------------|

