technical datasheet

AJAX

Wired volumetric detector

MOTIONCAM-FIBRA-W

TECHNICAL SPECIFICATIONS

Compatibility	**Ajax Fibra panels**
LED indicators	**Yes**
Tamper	**Dual**
Tiempo de intervalo para la conexión con el receptor	**12 ~ 300 sec**
Connection type	**BUS**
Protection against false alarms	**Yes, algorithmic analysis**
Transmission distance	**Up to 2000 m**

DETECTION

Detector type	**Wired**
Installation height	**2.4 m**
Angle detection	**88.5° Horizontal / 80° Vertical**
Detection distance	**12 m**
Detection speed	**0,3 m/s ~ 2 m/s**
Pets immunity	**Up to 20 kg and 50 cm**
Detection technology	**Volumetric**

POWER CONSUMPTION

Power mode	**DC (via Hub Hybrid BUS)**
Voltage	**24V**
Battery support	**Included**

VERIFICACIÓN FOTOGRAFICA

Picture quality	**640 × 480 / 320 × 240 (default) / 160 × 120**
Reception time of a photo	**Up to 9 sec**
Series images	**1 - 5 images**

MATERIAL AND DIMENSIONS

Dimensions	**135 x 70 x 66 mm**
Material	**Plastic**
Net weight	**140 g**
Weight with packaging	**190 g**
Color	**White**

AMBIENT

Operating temperature	**-10 °C ~ 40 °C**
Degree of protection	**IP50**
Use	**Indoor**
Maximum humidity	**75%**

SENSOR

Type of sensor	**PIR**
Sensitivity adjustment	**Sí**
Digital temperature compensation	**Yes**

CERTIFICATION

Grade	**2**
Normative	**EN50131**