

**HIKVISION**  
accessories



## 6 ports cloud switch with 4 PoE ports

DS-3T1306P-SI/HS

### REMOTE MANAGEMENT

P2P	<b>Yes</b>
Software	<b>Hik Pro Connect / IVSM4200</b>
Reset switch	<b>Yes</b>
PoE port reset	<b>Yes</b>
Extended mode activation	<b>Yes, independently per port</b>
Port speed modification	<b>Yes</b>
Actual power consumption	<b>Yes, total and per port</b>
History of peak consumption	<b>Yes (up to 7 days)</b>
Real-time traffic information	<b>Yes, by port</b>
Connected device information	<b>Yes, for Hikvision equipment (IP, model, and SN)</b>
Automatic topology diagram	<b>Yes, for connected Hikvision devices</b>

### CHARACTERISTICS (SWITCH)

Data rate supported	<b>14 Gbps</b>
Packet redirection speed	<b>10.42 Mpps</b>
VLAN	<b>Yes (max 4094 VLAN)</b>
Maximum transmission distance	<b>300 m</b>
Buffer Memory	<b>1 Mb</b>
PoE Watchdog	<b>Yes</b>
QoS	<b>Yes</b>
Industrial	<b>Yes</b>

### MATERIAL AND DIMENSIONS

Installation	<b>DIN rail / desktop</b>
Dimensions	<b>158 x 101.2 x 31.6 mm</b>
Material	<b>Metal</b>
Net weight	<b>390 g</b>
Weight with packaging	<b>960 g</b>

### NET STANDARD

IEEE802,3af	<b>Yes</b>
IEEE802,3at	<b>Yes</b>

### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>48V</b>
Consumption (w)	<b>65W</b>
Standby consumption	<b>5W</b>
Maximum consumption per port (PoE)	<b>30W</b>
Total maximum consumption (PoE)	<b>60W</b>

### ETHERNET PORTS

POE ports	<b>4</b>
Uplink ports	<b>1</b>
Fiber port	<b>1 x 1000</b>
POE Ports Speed	<b>10 / 100</b>
Uplink ports speed	<b>10/100/1000</b>
Number of Ethernet ports	<b>6</b>

### AMBIENT

Operating temperature	<b>-30 °C ~ 65 °C</b>
Use	<b>Indoor</b>
Maximum humidity	<b>95%</b>
Lightning protection	<b>6KV</b>

### SYSTEM (SWITCH)

MAC address table	<b>2K</b>
-------------------	-----------

