



PT ip camera of 4 megapixels and fix lens

SD3A400-GN-A-PV

VIDEO (CAMERAS)

Video Resolution	4 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	DWDR
Images per second	25fps
Video output	RJ45
Day / night mode	Colour
Type of Codex	CBR / VBR
Bit rate	H.264: 2304Kbps ~ 8192Kbps / H.265: 768Kbps ~ 6912Kbps
Compression	H.265 / H.264
Main stream	4Mpx / 1080P / 1.3Mpx / 720P (1 ~ 25fps)
Sub stream	D1 / CIF (1 ~ 25fps)

NIGHT VISION

Night vision distance	30 m
Type of night vision	Dual light (IR+Luz blanca)
Number of LEDs	2
IR ON/Off	Yes
Full Color	Yes
White light	2
White light distance	30 m
Smart Dual Illumination	Yes (switches from IR to colour with human detection)

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	13W
Amperage	1500mA

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, S and T type
Transmission method	Unicast / Multicast
Maximum number of users	20 users
Web browser	Explorer / Chrome / Firefox / Safari
Management software	DMSS
Mobile devices	Android / IOS (Apple)
Network disconnection	Yes
Conflict of IP addresses	Yes

IMAGE

Sensor	CMOS ®
Sensor resolution	2560 x 1440
Sensor Size	1/3'
Electronic shutter speed	1/3 ~ 1/1000000s
Minimum lighting	Color: 0.002Lux / B/W: 0.0002Lux
Ratio S / N	More than 55dB

PTZ

Pan / Tilt Range	Horizontal 355° / Vertical -15 ~ 90°
Manual speed control	Horizontal 0.1°/s ~ 26°/s / Vertical 0.1°/s ~ 17.5°/s
Speed between presets	Horizontal 26°/s / Vertical 17.5°/s
Memories	300
Position after power failure	Return to the position before the fault
Idle mode	Preset

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP66
Use	Indoor-outdoor
Maximum humidity	95%
Lightning protection	2KV

DISTANCE DORI

technical datasheet

PoE power	Yes
-----------	-----

Type PoE	PoE 802.3af
----------	-------------

VIDEO ANALYSIS

Detection type	Analytical with classification of person in line/area crossing
----------------	--

Crossing line	Yes
---------------	-----

Intrusion	Yes
-----------	-----

Motion detection	Yes
------------------	-----

Audio detection	Yes
-----------------	-----

Video Tamper	SI
--------------	----

LENS

Lens Type	Fix
-----------	-----

Focal distance	4 mm
----------------	------

Maximum diaphragm opening	F/1.6
---------------------------	-------

Angle of View	80.2°
---------------	-------

Minimum focus distance	300mm
------------------------	-------

GENERAL INFORMATION

Serie	LITE
-------	------

Technology	IP
------------	----

Type of camera	PT
----------------	----

AUDIO(CAMERAS)

Built in microphone	Yes
---------------------	-----

Built in speaker	Yes
------------------	-----

Audio compression	G.711A / G.711U / G.722.1 / G.726 / MPEG2-Layer2 / PCM
-------------------	--

TIOC

Siren	Yes
-------	-----

Light	White
-------	-------

Siren duration interval	5s ~ 30s
-------------------------	----------

Detect	55 m
--------	------

Observe	22 m
---------	------

Recognize	11 m
-----------	------

Identify	5 m
----------	-----

MATERIAL AND DIMENSIONS

Dimensions	271.7 x 165.5 x 140 mm
------------	------------------------

Net weight	1070 g
------------	--------

Weight with packaging	1465 g
-----------------------	--------

STORAGE

MicroSD-Card	Up to 256Gb
--------------	-------------

Storage Systems	FTP / Micro SD
-----------------	----------------

Storage anomaly	Yes
-----------------	-----

AXES

Motion	2-Axis
--------	--------

