

**HIKVISION**  
accessories



IP 7" monitor

DS-KH6350-WTE1

## POWER CONSUMPTION

|                 |             |
|-----------------|-------------|
| Power mode      | DC          |
| Voltage         | 12V         |
| Consumption (w) | 5W          |
| Amperage        | 1000mA      |
| PoE power       | Yes         |
| Type PoE        | PoE 802.3af |

## INPUTS/OUTPUTS

|                |              |
|----------------|--------------|
| Alarm input    | 8            |
| RS485          | 1            |
| Blocking entry | 2            |
| Alarm output   | 2            |
| RJ45           | 1 x 10 / 100 |

## SYSTEM (RECORDERS)

|                  |                    |
|------------------|--------------------|
| Processor        | Embedded Processor |
| Operating system | Embedded LINUX     |
| RAM              | 128 MB             |
| ROM              | 32 MB              |

## SCREEN

|            |            |
|------------|------------|
| Type       | TFT        |
| Size       | 7"         |
| Resolution | 1024 x 600 |
| Touch      | Sí         |

## NETWORK CHARACTERISTICS (INTERCOM MONITORS)

|                  |                      |
|------------------|----------------------|
| Network protocol | TCP / IP / RSTP      |
| Memory slot      | SD up to 128Gb       |
| Wi-Fi            | Sí                   |
| Tipo de Wi-Fi    | IEEE802.11 b / g / n |

## MATERIAL AND DIMENSIONS

|                       |                     |
|-----------------------|---------------------|
| Installation          | Desk / wall         |
| Dimensions            | 175 x 113.5 x 21 mm |
| Net weight            | 350 g               |
| Weight with packaging | 680 g               |

## CAPACITY

|                                   |     |
|-----------------------------------|-----|
| Events                            | 200 |
| Warnings                          | 200 |
| Linked phones                     | 17  |
| Extensiones interiores vinculadas | 16  |

## AUDIO (VIDEO INTERCOM)

|                     |                             |
|---------------------|-----------------------------|
| Sound input         | Omni-directional microphone |
| Sound output        | Built-in speaker            |
| Bidirectional audio | Sí                          |
| Audio compression   | G.711A / G.711U             |

## AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -10 °C ~ 50 °C |
| Use                   | Indoor         |
| Maximum humidity      | 90%            |

## GENERAL INFORMATION

|            |    |
|------------|----|
| Technology | IP |
|------------|----|

