



HIKVISION
intrusion

Wireless volumetric detector

DS-PDPC12PF-EG2-WE

DETECTION

Detector type	Wireless
Installation height	1.8 m ~ 2.4 m
Angle detection	90°
Detection distance	12 m
Detection speed	0,3 m/s ~ 2 m/s
Detection zones	52
Pets immunity	Up to 30 Kg
PIR detection advance at ground level (PIR Creep)	Sí

POWER CONSUMPTION

Power mode	Battery
Built in battery	Yes
Battery model	3 x CR123A , 3V
Battery duration	Up to 6 years

TECHNICAL SPECIFICATIONS

Compatibility	Hikvision panels
LED indicators	Yes
Tamper	Dual

VERIFICACIÓN FOTOGRÁFICA

Angle of view	88.4° horizontal / 54° vertical
Picture quality	640 × 480 / 320 × 240 / 160 × 120
ColorVu	Yes

VIA RADIO

Frequency	868mHz
Transmission distance	Up to 800 m (without obstacles)

MATERIAL AND DIMENSIONS

Installation	Wall / ceiling
Dimensions	72.2 x 120.5 x 56.7 mm
Net weight	165 g
Weight with packaging	270 g

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

SENSOR

Type of sensor	PIR
Sensitivity adjustment	Sí
Digital temperature compensation	Yes

CERTIFICATION

Grade	2
Environmental class	II

GENERAL INFORMATION

Serie	AXPRO
-------	--------------

