

**HIKVISION**
accessories

Smart Wi-Fi 6 access point

DS-3WAP522-SI

WI-FI

Wi-Fi standard	Radio 1: IEEE802.11 a / an / ac / Radio 2: IEEE802.11 b / g / gn
Frequency range	Radio 1: 5 GHz / Radio 2: 2.4 GHz
Broadband channel	Radio 1: Auto / 20 / 40 / 80 MHz / Radio 2: Auto / 20 / 40 MHz
Security	WPA-PSK / WPA2-PSK
Speed	Radio 1: 867Mbps / Radio 2: 300Mbps
Transmission distance	1200 m
Antenna	2 x Radio 1: 4 dBi / Radio 2: 3 dBi
Maximum number of clients	256 (80 recommended)
Maximum number of SSIDs	8

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	11.3W
Amperage	1500mA
PoE power	Yes
Type PoE	PoE 802.3af / PoE+ 802.3at

TECHNICAL CHARACTERISTICS

LED indicator	Yes
---------------	------------

MATERIAL AND DIMENSIONS

Dimensions	35 x 220 (Ø) mm
Net weight	370 g
Weight with packaging	710 g

AMBIENT

Operating temperature	0 °C ~ 40 °C
Maximum humidity	95%

INPUTS/OUTPUTS

RJ45	1 x 10 / 100 / 1000
------	----------------------------

