



HIKVISION
accessories

Wi-Fi 5 access point DS-3WF02C-5AC/O

WI-FI

Wi-Fi standard	IEEE802.11 a / n / ac
Frequency range	5.15 GHz ~ 5.25 GHz / 5.25 GHz ~ 5.35 GHz / 5.47 GHz ~ 5.725 GHz / 5.725 GHz ~ 5.85 GHz
Broadband channel	20 / 40 / 80 MHz
Security	WPA2-PSK
Speed	867Mbps
Transmission distance	5000 m
Angle	35°
Antenna	12dBi
MIMO	2 x 2

POWER CONSUMPTION

Consumption (w)	4.5W
Amperage	1000mA
PoE power	Yes
Type PoE	12V - 24V PoE
Power supply included	Yes

TECHNICAL CHARACTERISTICS

LED indicator	Yes
DIP Switch	Yes

ETHERNET PORTS

10 / 100 / 1000	2
-----------------	---

AMBIENT

Operating temperature	-30 °C ~ 70 °C
Degree of protection	IP55
Use	Indoor-outdoor
Maximum humidity	95%

MATERIAL AND DIMENSIONS

Dimensions	187.9 x 90.8 x 57.9 mm
Net weight	270 g
Weight with packaging	570 g

INPUTS/OUTPUTS

RJ45	1 x PoE / LAN, 1 x LAN
------	------------------------

SOFTWARE

Work Mode	Access Point / Repeater
-----------	-------------------------

