

HIKVISION®

6 ports switch with 4 PoE ports

DS-3E0106HP-E



POWER CONSUMPTION

Power mode	DC
Voltage	48V
Consumption (w)	65W
Amperage	1350mA
Standby consumption	5W
Maximum consumption per port (PoE)	Port 1 ≤ 60W / Ports 2 ~ 4 ≤ 30W
Total maximum consumption (PoE)	60W
Power supply included	Yes

MATERIAL AND DIMENSIONS

Dimensions	145 x 25.6 x 68.45 mm
Material	Metal
Net weight	240 g
Weight with packaging	770 g

CHARACTERISTICS (SWITCH)

Data rate supported	1.2 Gbps
Packet redirection speed	0.89 Mpps
Maximum transmission distance	300 m
Buffer Memory	768K

GENERAL INFORMATION

Serie	HikS-C
-------	---------------

PROTECTION AGAINST RAYS

ESD contact to electronic board	6KV
---------------------------------	------------

ETHERNET PORTS

POE ports	4
Uplink ports	2
Hi-PoE	Port 1
Number of Ethernet ports	6

AMBIENT

Operating temperature	0 °C ~ 40 °C
Use	Indoor
Maximum humidity	95%

NET STANDARD

IEEE802,3af	Yes
IEEE802,3at	Yes
IEEE802.3bt	Yes

SYSTEM (SWITCH)

MAC address table	2K
-------------------	-----------

